



The Culligan Hi-Flo® 50 Series Industrial Dealkalizer System



EXAMPLES OF MARKETS SERVED:

- CLINICS
- EDUCATIONAL FACILITIES
- ENERGY & POWER
- FOOD & BEVERAGE PRODUCTION
- FOOD SERVICE/RESTAURANTS
- GROCERY
- HEALTHCARE/HOSPITALS/BIO-PHARMACEUTICAL
- HOSPITALITY/LODGING
- MANUFACTURING
- MUNICIPAL DRINKING WATER
- OIL & GAS

Reduced Alkalinity for High-Volume Applications

The Culligan Hi-Flo 50 dealkalizer reduces alkalinity in water used for commercial and industrial applications. The Hi-Flo 50 dealkalizer is a post-treatment option for your Culligan water softening system that further reduces contaminants* in the water that affect the performance and efficiency of water-using equipment. The scalable configuration helps meet your growing needs for high-quality water. Manage the Hi-Flo 50 dealkalizer system with the Culligan-exclusive Smart Controller that is easy to program and use.

The Hi-Flo 50 dealkalizer is part of the Culligan Matrix Solutions™ that combine durable and efficient equipment, systems experience, and technical experts who understand your unique requirements. From planning your system to installing your water treatment equipment, Culligan Matrix Solutions offer options that help deliver the quality of water to meet your needs. Contact Culligan today to learn more about the Hi-Flo 50 dealkalizer.

*contaminants may not necessarily be in your water

Culligan Matrix Solutions Advantages:

- Simple System Integration
- Global Product Platform
- Flexible Configurations
- Quick Delivery/Easy Installation
- Exclusive Culligan Advanced Electronics
 - Historical Operating Data
 - Alarm Recognitions
 - US Standard and Metric Readings
 - Remote Monitoring Options
 - Telemetry Options



**Pre-Treatment
Solutions**



Membrane
Solutions



Deionization
Solutions



Storage
Solutions



Distribution
Solutions

Warranty

Culligan's Hi-Flo 50 dealkalizers are backed by a limited 1-year warranty against defects in material, workmanship and corrosion. In addition, tanks are warranted for a period of 5 years.†

†See printed warranty for details. Culligan will provide a copy of the warranty upon request.

Examples of Dealkalizer Applications

- Boiler and Cooling tower make-up water — Lower energy costs
- Manufacturing — Water treatment for consistent production
- Food Manufacturing ingredient, process and utility water treatment
- Process water treatment

Standard Features

- Single or Multiple Tank Configurations — Flow rates up to 200 gpm per tank
- Culligan's Smart Controller — More control over your equipment with programming and monitoring capabilities typically found in more expensive PLC controls, a variety of add-on options for advanced instrumentation and communication let you easily customize the system to help meet your needs
- Regeneration initiation by choice or combination of time clock or meter
- Telemetric Capability
- Side-Mounted Valve Harness — Guided perimeter designed diaphragm valves are smooth operating and free of water hammer, all valve parts are easily accessible in the design for ease of service
- Corrosion resistant tanks — Made of low carbon steel with epoxy interior lining and finish coat painted exterior

Optional Features & Accessories

- Corrosion resistant brine system construction for long life
- Skid Mounted — Fully pre-piped and wired systems for single point field utility connection of inlet, outlet, drain and power supply
- Patented Progressive Flow — Culligan's Smart Controller can monitor flow demands bringing additional tanks on-line or offline as flows increase or decrease
- ASME Code Tanks
- Brine Reclaim — Reduces operating costs by recycling a portion of the regeneration water
- Flow Measuring Devices — Available for volume based regeneration initiation
- Gauge Packages — Pressure gauges provided for mounting at the inlet and outlet connection
- Remote Display
- RS232, RS485, Modbus PLC Output

System Specifications

Specification	US	Metric
Inlet Pressure (dynamic)	30-120 psig	210-830 kPa
Power Voltage Frequency Phase	120 VAC/24 VAC ¹ 50/60Hz	
Feed Water Temperature	40–120° F	4-49° C
Turbidity, maximum	5 NTU	
Chlorine, max.: 0 mg/L	1 mg/l	
Iron, maximum	5 mg/l	

¹ 120 Volt/24 Volt CUL/UL listed Transformer Included.
² See media specification for details.

Hi-Flo 50 Dealkalizer System

Model	Resin Qty. (Ft ³ /L)	Pipe Size (in/mm)	Flow Rates (gpm@psi / lpm@kPa)		Tank Size (in/mm)	
			Continuous*	Peak**	Resin Tank	Brine Tank***
CA-483	35	3	60 @ 4	120 @ 7	48 x 60	48 x 60
	991	3	227.1 @ 27.6	454.2 @ 48.3	1,219 x 1,524	1,219 x 1,524
CA-543	44	3	80 @ 5	160 @ 10	54 x 60	48 x 60
	1246	3	302.8 @ 34.5	605.6 @ 68.9	1,372 x 1,524	1,219 x 1,524
CA-604	54	4	100 @ 6	200 @ 12	60 x 60	60 x 60
	1529	4	378.5 @ 41.4	757 @ 82.7	1,524 x 1,524	1,524 x 1,524

* Flow rate is based on pressure drop.

** Flow rate is based on pressure drop.

*** Dimensions are diameter by tank height.

**** Per Tank

Flow rates shown are per tank.

Low flow channeling (flow rates less than 0.5 gallons per minute per cubic foot of resin) may cause leakage into effluent.

Finally, an end-to-end solution from a single source.



Place your commercial and industrial water treatment needs in the hands of a global leader.

For over 70 years, Culligan has made better water. Our global network, comprised of 800+ dealers and international licensees in over 90 countries, is dedicated to addressing your water-related problems. As a worldwide leader in water treatment, our sales representatives and service technicians are familiar with the local water conditions in your area. Being global and local position us to deliver customized solutions to commercial and industrial water issues that affect your business and your bottom line.

www.culliganmatrixsolutions.com • 866-787-4293

RR Donnelley # 46908 Print 02/10 ©2010 Culligan International Company.

All trademarks used herein are registered trademarks of Culligan International Company. Products manufactured or marketed by Culligan and its affiliates are protected by patents issued or pending in the United States and other countries. Culligan reserves the right to change the specifications referred to in this literature at any time, without prior notice.



Printed on recycled paper